

ENDURAPLAS
ADVANTAGE
TOW LYNX® 365



■ WA055FG225GH ■ WA075FG225GH ■ WA100FG225GH

DESIGNED BETTER. BUILT STRONGER. LASTS LONGER.

**QUICK-CONNECT™
 BOOM PORTS**

Built-in boom connection points to save time and hassle when removing and attaching a spray boom.

**AUTO-DRAIN™
 SUMP BASE**

The sloped tank base channels every ounce of liquid to drain. Just where it should go.

**MAX-FLOTATION™
 ATV TIRES**

With beefed up tires, rough terrain is not a concern. Every bump and thud is accounted for.



**SPRAY-COMMAND™
 CONTROLS**

Select where you want to spray and at what pressure with all controls within reach.

**EASY-START™
 HONDA®
 ENGINE**

Within the first few pulls, this trusty, reliable engine is guaranteed to start. Even after a long Winter.

**HEFTY-BUILT™
 CHASSIS**

This durable frame is over-built so it won't bend or bust when spraying on rugged ground.

50 PSI	22.5 GPM	27' VERTICAL SPRAY	35' HORIZONTAL SPRAY	\$
------------------	--------------------	---------------------------------	-----------------------------------	----

PRODUCT CODE	TANK SIZE (GAL)	DIMENSIONS (L X W X H)	MOTOR	PUMP	FLOW RATE (GPM)	PSI	HITCH SIZE	TIRES	HOSE LENGTH	SPRAY DISTANCE VERTICAL	SPRAY DISTANCE HORIZONTAL	DRY WEIGHT (LBS)
WA055FG225GH	55	80" x 51" x 38"	GX120 Honda/4 HP	Centrifugal	22.5	50	1 7/8" Ball	ATV	50'	27'	35'	220
WA075FG225GH	75	80" x 56" x 43"	GX120 Honda/4 HP	Centrifugal	22.5	50	1 7/8" Ball	ATV	50'	27'	35'	305
WA100FG225GH	100	91" x 60" x 40"	GX120 Honda/4 HP	Centrifugal	22.5	50	1 7/8" Ball	ATV	50'	27'	35'	325

*Double your 5 yr tank warranty when you register this product. *All Enduraplas poly tanks are manufactured in the United States of America.



ENGINEERED FOR ENDURANCE®

www.enduraplas.com
 info@enduraplas.com
 1 (877) 877-4370